


LTTng 2.0 and LTTngTop Current Status



Mathieu Desnoyers

David Goulet

Julien Desfossez

Yannick Brosseau

*December 9, 2011
École Polytechnique, Montreal*

Content

- Main goals reminder
- Architecture
- Current status
- Future work
- Demos




LTTng 2.0: Main goals

- Unified interface for kernel and userspace
- Common Trace Format (CTF) suitable for software and hardware tracers
- Improve the user experience
- Remove the need for kernel patches, to ease the integration into distributions



LTTng 2.0 Low-Overhead Tracing Architecture



*** Tracepoint and Probes Characteristics**

- Low overhead, no trap, no system call,
- Re-entrant: Signal, thread and NMI-safe,
- Wait-free read-copy update,
- Can be used in real-time systems,
- Use GCC asm goto and Linux kernel static jumps,
- Cycle-level time-stamp,
- Runtime activation of statically and dynamically inserted instrumentation,
- Non-blocking atomic operations,
- Allow tracing of proprietary applications and proprietary control software (GPLv2.1 license).

† Common Trace Format (CTF)

- Compact binary format,
- Self-described,
- Handles HW&SW tracing,
- TCP and UDP network streaming,
- Flexible data layouts for expressiveness and highest throughput,
- Layout allows fast seek and processing of very large traces (> 10GB).

Instrumentation

Control

Trace Data

Libraries

Current Status

- Kernel tracing:
 - Context
 - Syscall
 - Kprobes
 - Function tracer
- Userspace:
 - Loglevel
 - Wildcard activation
 - Automatic application registration
 - Automatic tracepoint activation on registration



Current Status (2)

- Viewers:
 - Babeltrace
 - LTTngTop
 - cputop, perfstop, lotop
 - offline, live
- Distributions
 - Daily packages in LTTng Ubuntu PPA



Demos

LTTng 2.0
LTTngTop



Future plans

- New prerelease bundle with UST next week
- Networked consumer
- Trace clock (Kernel infrastructure + CTF description)
- System wide per user buffer for UST
- Data aggregation
- Statedump
- LTTV

